



FEMMINA DIRITTA - CONO 60° O.R. DADO SFILABILE FILETTO GAS CILINDRICO	DKOR 60° KONUS MIT O-RING (BSP GEWINDE) HINTERLEGTE MUTTER	BSP O-RING FEMALE 60° CONE (SLIP-ON NUT)	RACCORD FEMELLE DROITE CONE 60° O.R. ECROU DETACHABLE FILETAGE BSP CYLINDRIQUE	RACOR HEMBRA DERECHA CONO 60° O.R. TUERCA SEPARABLE ROSCA CILÍNDRICA DE GAS						
		CODICE ZEICHEN REFERENCE DESCRIPTION CODIGO	Ø Tubo Rohr ID - Hose I.D. Ø Tube - Ø Tubo		Ø F	CH	Ø d	M	H	L ≈
		600550404	1/4	6	1/4	19	4	5,4	17	50
		600550606	3/8	10	3/8	22	7	6	20,5	54
		600550808	1/2	13	1/2	27	10	6,5	22,5	58
		600551212 (2)	3/4	19	3/4	32	15,5	7,5	25,5	72
		600551616 (2)	1"	25	1"	38	20	10	26,5	89
		600552016 (3)	1"	25	1" 1/4	50	20	11,5	32,5	96,5
		600552020 (3)	1" 1/4	32	1" 1/4	50	26	11,5	33	102,5
		600552424 (3)	1" 1/2	38	1" 1/2	55	32	11	35	116
600553232 (3)	2"	50	2"	70	44	16	31	121,5		

1) Zoll - Inches - Pouces - Pulgadas

(2) Dado graffato - Pressmutter - Crimped back nut - Ecrou agrafé - Tuerca suetada con grapa

(3) Dado spinato - Gestiftete mutter - Thrust wire nut - Ecrou à cheville - Tuerca sujedada con perno