



FEMMINA CURVA 90° CONO 60° O.R. DADO SFILABILE FILETTO GAS CILINDRICO	DKOR 90° BOGEN 60° KONUS MIT O-RING (BSP GEWINDE) HINTERLEGTE MUTTER	90° BSP O-RING FEMALE ELBOW 60° CONE (SLIP-ON NUT)	RACCORD FEMELLE TORDUE 90° CONE 60° O.R. ECROU DETACHABLE FILETAGE BSP CYLINDRIQUE	RACOR HEMBRA CURVA 90° CONO 60° O.R. TUERCA SEPARABLE ROSCA CILÍNDRICA DE GAS						
	CODICE ZEICHEN REFERENCE DESCRIPTION CODIGO	Ø Tubo Rohr ID - Hose I.D. Ø Tube - Ø Tubo		Ø F	CH	Ø d	M	K ≈	H ≈	L ≈
		Pollici (1)	mm							
	600560404	1/4	6	1/4	19	4	5,4	28	23	50,5
	600560606	3/8	10	3/8	22	7	6	37	30,5	59
	600560808	1/2	13	1/2	27	10	6,5	43,5	38	68
	600561212 (2)	3/4	19	3/4	32	15,5	7,5	58	54	93
	600561616 (2)	1"	25	1"	38	20	10	70,5	74	126,5
	600562016 (3)	1"	25	1" 1/4	50	20	11,5	78,5	74	126,5
	600562020 (3)	1" 1/4	32	1" 1/4	50	26	11,5	88,5	80	140
	600562424 (3)	1" 1/2	38	1" 1/2	55	32	11	103,5	93	163
600563232 (3)	2"	50	2"	70	44	16	124	129	203,5	

(1) Zoll - Inches - Pouces - Pulgadas

(2) Dado graffato - Pressmutter - Crimped back nut - Ecrou agrafé - Tuerca suetada con grapa

(3) Dado spinato - Gestiftete mutter - Thrust wire nut - Ecrou à cheville - Tuerca sujedada con perno