



FEMMINA CURVA 45° CONO 60° O.R. DADO SFILABILE FILETTO GAS CILINDRICO	DKOR 45° BOGEN 60° KONUS MIT O-RING (BSP GEWINDE) HINTERLEGTE MUTTER	45° BSP O-RING FEMALE ELBOW 60° CONE (SLIP-ON NUT)	RACCORD FEMELLE TORDUE 45° CÔNE 60° O.R. ÉCROU DÉTACHABLE FILETAGE BSP CYLINDRIQUE	RACOR HEMBRA CURVA 45° CONO 60° O.R. TUERCA SEPARABLE ROSCA CILÍNDRICA DE GAS														
					CODICE ZEICHEN REFERENCE DESCRIPTION CODIGO	Ø Tubo Rohr ID - Hose I.D. Ø Tube - Ø Tubo		Ø F	CH	Ø d	M	K ≈	H ≈	L ≈				
					Pollici (1)	mm												
					600570404	1/4	6	1/4	19	4	5,4	14,5	37,5	65				
					600570606	3/8	10	3/8	22	7	6	19	50	78,5				
					600570808	1/2	13	1/2	27	10	6,5	21,5	62	92				
					600571212 (2)	3/4	19	3/4	32	15,5	7,5	28	64	103				
					600571616 (2)	1"	25	1"	38	20	10	33	85	137,5				
					600572016 (3)	1"	25	1" 1/4	50	20	11,5	39	90,5	143				
					600572020 (3)	1" 1/4	32	1" 1/4	50	26	11,5	42	99,5	159,5				
600572424 (3)	1" 1/2	38	1" 1/2	55	32	11	48	112	182									
600573232 (3)	2"	50	2"	70	44	16	52,5	132,5	207									

(1) Zoll - Inches - Pouces - Pulgadas

(2) Dado graffato - Pressmutter - Crimped back nut - Ecrou agrafé - Tuerca suetada con grapa

(3) Dado spinato - Gestiftete mutter - Thrust wire nut - Ecrou a cheville - Tuerca sujedada con perno